

Motorbike 4T Synth 5W-40 Street Race

Description

Fully synthetic high-performance motor oil. Ensures maximum performance and protection of the engine under all operating conditions. Optimum lubrication, outstanding engine cleanliness, excellent friction and minimum wear are just as much taken for granted as gentle clutch engagement and disengagement and gear shifting. That makes a big difference to driving enjoyment! Tested on engines with catalytic converters. Tested on racing machines.

Properties

- tested for catalytic converters
- optimum stability to aging
- high engine cleanliness
- guarantees low oil consumption
- optimum lubrication under all operating conditions
- excellent shear stability
- especially suitable for wet clutches
- excellent wear resistance

Specifications and approvals:

ACEA A3 • API SM • JASO MA2

Technical data

| | |
|---------------------------|---|
| SAE class (engine oils) | 5W-40 SAE J300 |
| Density at 59 °F | 0,850 g/cm ³ DIN 51757 |
| Viscosity at 104 °F | 90.2 mm ² /s ASTM D 7042-04 |
| Viscosity at 212°F | 14,5 mm ² /s ASTM D 7042-04 |
| Viscosity at -31 °F (MRV) | <= 60000 mPas ASTM D4684 |
| Viscosity at -22 °F (CCS) | <= 6600 mPas ASTM D5293 |
| Viscosity index | 167 DIN ISO 2909 |
| HTHS at 302 °F | >= 3,5 mPas ASTM D5481 |
| Pour point | -49 °F DIN ISO 3016 |
| Evaporation loss (Noack) | 7.0 % CEC-L-40-A-93 |
| Flash point | 446 °F DIN ISO 2592 |
| Total base number | 10,5 mg KOH/g DIN ISO 3771 |



Technical data

| | |
|---------------------|-------------------------------|
| Sulfate ash | 1,0 - 1,6 g/100g DIN 51575 |
| Color number (ASTM) | L4,0 DIN ISO 2049 |

Areas of application

Developed for air and water-cooled 4-stroke engines exposed to normal to extreme operating conditions. For sporting applications. Suitable for engines with or without a wet clutch.

Application

The operating instructions of the engine manufacturers must be followed.

Note: Optimum effectiveness only when the product is used on its own (i.e. no mixing).

Available pack sizes

| | |
|------------------------|-------------------------|
| 1 l Canister plastic | 20074 GB-F-E-USA-CAN |
| 4 l Canister plastic | 20076 GB-F-E-USA-CAN |
| 20 l Canister plastic | 2720 D-GB-I-E-P |
| 20 l Canister plastic | 20304 GB-F-E-USA-CAN |
| 60 l Drum sheet metal | 2593 D-GB |
| 205 l Drum sheet metal | 2594 D-GB |

Our information is based on thorough research and may be considered reliable, although not legally binding.